Highchair Assembly Instructions



Juno Bambino

CONTENTS

QTY	DESCRIPTION	COMPONENT REF:
2	Welded Tube sides	Side
1	Back Board	Back
1	Seat Board	Seat
1	Longest Length Rail	R1
1	Medium Length Rail	R2
1	Smallest Length Rail/Barrier	R3
6	30mm M6 Screws for Frame	Frame Screw

QTY	DESCRIPTION	COMPONENT REF:
4	35mm M6 Screws for Seat	Seat Screw
2	35mm M6 Screws for Back	Back Screw
4	M6 Washers	Washer
4	Stacking Bungs	Stacking Bung
1	Seat Strap	Seat Strap
1	Allen Key	Allen Key

STEP 1


Place one of the sides vertically on the floor with the back panel slot facing away from you.



STEP 2


Use two of the four supplied seat screws and place one washer and stacking bung on each of them.

Proceed to loosely secure the seat board to the side using these screws.




STEP 3

Loosely attach the three rails to the side using the supplied screws. The sticker on the rails should be positioned to the bottom of the Highchair. Note: top rail must slide through seat strap loop.




STEP 4

Lay the highchair on its side and repeat step 3 to loosely attach other side to frame. Repeat step 2 to loosely attach the remaining 2 seat screws.



STEP 5

Place the back panel into the slot between the bars and attach with supplied back screws.



STEP 6

Tighten all screws to secure the frame. Note: Do not over tighten stacking bungs.



Helo Products Ltd Fountain Way, Reydon Business Park, Reydon, Southwold, Suffolk, IP18 6SY. Telephone: +44 (0) 1284 772400 e-mail: sales@hel-o.co.uk www.hel-o.co.uk

Registered in England No. 13058754 VAT No. GB375 3632 81