



62061




64070



63004




63072




64150




64068



64045



65071



65069



65070



66119




66117




66039




65072




67066



68003



68030



68035




62060



61107



61004



60999



60016



60003



67066

**Composizione** Lana della Nuova Zelanda 100%**Peso** 800 gr/mtl**Altezza** 140 cm**Resistenza all'abrasione
Martindale ISO 12947-2/ISO 14465** 50.000 cicli**Solidità alla luce
xeno - ISO 105 B02** 5-7**Certificati di acustica
e fonoassorbenza** ISO 354
EN 29053

UNI 9175 Classe 1IM
EN 1021-1+2:2006
DIN 4102 Classe B2
BS 5852 IS 0+1
BS 476 Part. 7 Classe 1
California TB 117:2013
NFPA 286
B1-B2 Önorm B 3825 - Q1 Önorm A 3800
FTP Code 307(88):10 Annex 1 Part. 8
IMO RES.A. 652 (16)
MED certificate IMO
ASTM E 84


Non spazzolare. Usare con regolarità
l'aspirapolvere a beccuccio liscio.

Manutenzione

Fonoassorbente.
Materiale naturale che per le sue caratteristiche
tecniche può formare pilling asportabile utilizzando
una comune macchinetta mangiapelucchi.

Particolarità

Grado di resistenza all'uso:
intenso ●●●

Indicato per uso contract**Composition** Wool of New Zealand 100%**Weight** 800 gr/lmt**Width** 140 cm**Abrasion test
Martindale ISO 12947-2/ISO 14465** 50.000 cycles**Lightfastness
xeno - ISO 105 B02** 5-7**Acoustic test sound absorption
and air flow resistance** ISO 354
EN 29053

UNI 9175 Class 1IM
EN 1021-1+2:2006
DIN 4102 Class B2
BS 5852 IS 0+1
BS 476 Part. 7 Class 1
California TB 117:2013
NFPA 286
B1-B2 Önorm B 3825 - Q1 Önorm A 3800
FTP Code 307(88):10 Annex 1 Part. 8
IMO RES.A. 652 (16)
MED certificate IMO
ASTM E 84


Do not brush. Use vacuum-cleaner with
smooth spout regularly.

Maintenance

Sound absorbing.
Natural material. For its technical
features it could pill; in case use
any fabric pilling shaver/remover.

Features

Wear and tear resistance:
extreme ●●●

**Fabric for commercial
and Horeca use**